

REMARKS

ELECTION/RESTRICTION

The Examiner believes that five species are included as a part of the proposed Valley Truss Uplift Resistance Strap With Wedge invention herein, as follows:

Group 1:	Figs. 1-4	Group 2:	Figs. 5-9	Group 3:	Figs. 10-12
Group 4:	Figs. 13-19	Group 5:	Figs. 20-21		

The applicants herein disagree with the Examiner's preliminary conclusion that all embodiments presented as a part of the original disclosure are patentably distinct, and they provide a traverse below, with a request for reconsideration. However, since an Election is required as a part of the Office Action response regardless of whether a traverse is made, the applicants herein elect Group 4, as shown in Figs. 13-19.

As defined in the original claim 1, the applicants' uplift resistance device comprises a one-piece strap for use in supporting and tying-down manufactured valley truss components to supporting structural woods members and manufactured wood roof truss systems. The advantage of the proposed strap over the prior art is that it can be installed from a position solely above a roof plane and without cutting holes in plywood attached to standard roof trusses and without beveling modification for roof pitch. Each present invention strap has a substantially planar web member extending upwardly at an acute angle from a substantially planar base member, with a wedge formed between the base member and the web member. The wedge has a taller end and an opposed tapered end, with the taller end being adjacent to the web member. Also, the base member extends rearwardly beyond the taller end of said wedge. In addition, fastener holes are formed through the base member and the web member.

Fig. 1 shows a first embodiment uplift resistance device ready for use, while Figs. 2-4 show the device of Fig. 1 as it would appear and be positioned in use. In the original disclosure on page 9, lines 14-19, variations in structure for the uplift resistance device are discussed, as follows: "It is contemplated for the present invention to be made of rigid materials and have a unitary construction. However, the present invention can be made from plastic, nylon and other materials formed through molded construction, or in the alternative made from a stamped piece of rigid material, preferably galvanized steel, that is pre-formed into the approximate configuration shown in Fig. 1." Further, in the original disclosure on page 9, lines 25-26, additional variations in structure for the uplift resistance device are discussed, as follows: "The wedge can be solid or hollow, depending upon the materials used for its construction." Additional and similar structural language is provided on page 10, lines 25-26 and through page 11, line 1, as follows: "It is contemplated that first embodiment 2 would be made from molded construction, using metal, plastic, nylon, or any other material permitted by code. One preferred plastic material is polycarbonate." Thus, although Fig. 1 appears to have a hollow wedge construction, the original disclosure explains that an alternative embodiment could have a solid wedge, such as the Fig. 22 proposed herein.

The following paragraph discusses the differences between Groups 1 and 4. The definition of the applicants' uplift resistance device in the original claim 1 is consistent with the device shown in Fig. 1. It is a one-piece strap having a substantially planar base member, a substantially planar web member extending upwardly at an acute angle from the base member, and a wedge formed between the base member and the web member. The wedge has a taller end and an opposed tapered end, with the taller end being adjacent to the web member. Also, the

base member extends rearwardly beyond the taller end of said wedge. In addition, fastener holes are formed through the base member and the web member. The definition in claim 1 specifies that the base member extend rearwardly beyond the taller end of said wedge. However, there is no limitation about whether the base member should extend forwardly beyond the tapered end of the wedge. Therefore, the device shown in Fig. 1 and the device shown in Fig. 15 both fit within the definition of original claim 1, as the three visible differences in structure do not provide patentably different distinctions. The first such difference is no forward base member extension in Fig. 15, and as previously mentioned there is no limitation as to the length of the base member or the positioning of the wedge relative to the base member in the original claim 1, therefore, such a difference alone should not make Fig. 1 and Fig. 15 patentably distinct from one another. Differences in positioning of the present invention wedge relative to the base member would be determined by use of differing manufacture methods, none of which are included as a part of the claims within this patent application. The methods included as a part of this patent application are all methods of use. The second visible difference between Fig. 1 and Fig. 15 is a shorter rearward base member extension in Fig. 15. As mentioned before, there is no limitation as to the length dimension for the portion of the base member extending rearwardly beyond the taller end of said wedge in the original claim 1. Therefore, the second difference alone should not be considered as sufficient to make Fig. 1 and Fig. 15 patentably distinct. The third visible difference between Fig. 1 and Fig. 15 is the use of chamfered edges for the rear end of the base member and the top end of the web member in Fig. 1. Although chamfered edges serve a function and eliminate the sharp corners that might injure an installer, chamfered edges were not made a part of the original claim 1, and the applicants do not consider this to be a critical feature

of their invention.

The following paragraph discusses the differences between Groups 1 and 2. Figs. 5-9 show an embodiment of the present invention that is folded from a stamped piece of rigid material. The usable end configuration of the valley truss uplift resistance device in Group 2 is substantially the same as that shown in Fig. 1. For the reason of unnecessary duplication in the drawings, separate illustrations for such end configurations were not included as a part of the original disclosure. On page 14, lines 5-6 of the original Specification, it is stated that "When folding is complete, wedge 8 in second embodiment 24 would have the same hollow configuration shown in Fig. 1." When viewing Figs. 5-9, the only aspect of the final configuration made that is not readily determined is the shape of the wedge, although it can be seen in Fig. 9 substantially as it will appear in the formed product. Therefore, the device shown in Fig. 1 and the device made from the folding steps shown in Fig. 15 both fit within the definition of original claim 1, with only two visible differences in final structure that the applicants do not consider as patentably different distinctions. The first such difference is that the base member in Fig. 9 is reinforced with a second layer of material. The definition of the proposed invention herein, as stated in the original claim 1, includes a 'base member' and does not provide a limitation that such base member must have only one layer. Therefore, since such a difference is only as a result of the method of manufacture used and does not provide a functional difference in device structure, the applicants argue that the difference of a dual-layer base member should not make the embodiment in Fig. 2 patentably distinct from that in Fig. 1. The second visible difference between the embodiments in Fig. 1 and Fig. 9 is the use of chamfered edges for the rear end of the base member and the top end of the web member in Fig.

1, whereas such edges in Fig. 9 are rounded. The difference between rounded and chamfered edges makes no functional difference in the use of the present invention and the applicants herein argue that such a difference does not make the two embodiments patentably distinct from one another.

The following paragraph discusses the differences between Groups 1 and 3. Figs. 10-12 also show an embodiment of the present invention that is folded from a stamped piece of rigid material. However, the base member formed by the steps shown in Figs. 10-12 does not have a dual-layered construction. The usable end configuration of the valley uplift resistance device in Group 3 is substantially the same as that shown in Fig. 1. For the reason of unnecessary duplication in the drawings, separate illustrations for such end configurations were not included as a part of the original disclosure. On page 14, lines 25-26 and page 15, line 1 of the original Specification, it is stated that "Fig. 12 shows second end 6 and first end 4 almost aligned with one another as they would be when third embodiment 26 has reached its final configuration, similar to that shown in Fig. 1, with third embodiment 26 having a hollow wedge 8." For all of the applicable reasons stated above, the applicants herein argue that since the third embodiment device can read on claim 1, that it should not be considered patentably distinct from the embodiments distinguished by the Examiner as Group 1, Group 2, and Group 4.

The following paragraph discusses the differences between Groups 1 and 5. The valley uplift resistant devices shown in Fig. 20 are viewed from a distance and from the rear, so that detail in structure is not evident. As noted in the original Specification disclosure, the devices shown could represent the embodiment shown in Fig. 1, another embodiment, or a combination thereof, as follows: "Fig. 20 shows several present invention uplift resistance straps. such as first

embodiments 2. each connected between the horizontally extending bottom chord of a manufactured valley truss 16 and the top chord of a standard roof truss 18.” The point of including Figs. 20 and 21 as a part of the original disclosure was to demonstrate use of the device in an actual ‘valley’ situation. As such, the applicants argue that there is no separate embodiment structure in Figs. 20 and 21 that should be viewed as a patentably distinct embodiment.

NEW ILLUSTRATION – Fig. 22

The following paragraph discusses the differences between elected Group 4 and the molded embodiment shown in the newly proposed Fig. 22, submitted herein for filing. As can be seen in Exhibit “A”, both embodiments are visually similar although no holes have yet been formed through the folded embodiment on the left. Both have an upstanding web member, a wedge, and a base member extending rearwardly beyond the wedge. As such, both read on the original claim 1 and should be permitted examination as a part of the same invention. Marked-Up and Clean Copies of the Brief Description of the Drawings, as well as the Detailed Description of Preferred Embodiments have also been included for the addition of two sentences relating to Fig. 22. Also, the Marked-Up and Clean Copies make a spelling correction for ‘polycarbamate’, which should have been ‘polycarbonate’.

CONCLUSION

Since the applicants herein have provided a traverse that the applicants believe should have demonstrated that all of the embodiments shown in the originally filed drawings are a part of the same patentable invention, and that the newly proposed Fig. 22 for a molded embodiment

should not be considered as a patentably distinct embodiment or to include new matter, the applicants respectfully request that all embodiments presented herein be allowed to undergo examination together as a part of the same invention. The applicants believe that the initial confusion by the Examiner was a result of an attempt on the part of the applicants to avoid unnecessary duplication of illustrations, and that adding the newly proposed Fig. 22 for a molded embodiment should help in avoiding similar confusion by a reader after allowance and issue. For all of the reasons stated herein above, the applicants respectfully request reconsideration by the Examiner of the election/restriction requirement, and that all of the embodiments shown in Groups 1-5, as well as that in newly proposed Fig. 22, now be permitted to undergo examination together as a part of same above-identified patent application.

Respectfully prepared and submitted on behalf of
Timothy M. Bronson and Brian V. Fiala by:

A handwritten signature in black ink, appearing to read "Dorothy S. Morse". The signature is fluid and cursive, with the first name "Dorothy" and last name "Morse" clearly distinguishable.

Dorothy S. Morse, Esq.
515 Park Drive, N.W.
Bradenton, FL 34209-1847
phone: 941-747-4313
fax: 941-748-4008
U.S. Patent and Trademark Office Registration
Number: 38,977

FACSIMILIE COVER SHEET

DATE: 06/26/03TIME: 1205 a.m. / (p.m.)

FROM: Dorothy S. Morse, Esq.
515 Park Drive, N.W.
Bradenton, FL 34209-1847
phone: (941) 747-4313 / fax: (941) 748-4008

SEND TO: Carl Friedman, Examiner
U.S. Patent & Trademark Office
Phone: 703-308-0839
Fax: 703-308-3519

TOTAL PAGES SENT: 40 (including cover sheet)

☐ URGENT
☐ REPLY ASAP
☐ PLEASE COMMENT

☒
☒

PLEASE REVIEW
FOR YOUR INFORMATION
PER YOUR REQUEST
FOR FILING

COMMENTS:

Per my phone conversation with you earlier today, I am re-faxing a copy of the Office Action response for the patent application referenced below, which had been previously faxed to the USPTO on Friday, February 28, 2003. I just finished sending it to the Official fax number you gave me, and my Fax Log Report shows all pages being successfully transmitted.

To you I now include the original 36-page transmission, a copy of my Fax Log Report showing a successful transmission to both fax numbers on Feb. 28, 2003, the fax cover sheet to the Official Fax number you gave me earlier today and a copy of its Fax Log Report, plus the current fax cover sheet, a total of 40 pages in all. Contact me if you have any questions.


FOR -

Applicant: Timothy M. Bronson and Brian V. Fiala
Serial Number: 10/044,108
Date Filed: January 11, 2002
Title: Valley Truss Uplift Resistance Strap With Wedge and Method of Use
Examiner: Christy M. Green
Group Art Unit: 3635

NOTE: THE INFORMATION CONTAINED IN THIS FACSIMILIE TRANSMISSION IS
CONFIDENTIAL. IF YOU HAVE RECEIVED THIS INFORMATION IN ERROR, PLEASE NOTIFY
EITHER THE SENDER OR INTENDED RECEIVER AT ONCE. THANK YOU.

ERROR ON Pg 14
refaxed
14-40 at
1216pm 46/second
copy of this
fax cover
sheet

FOLDED
CONSTRUCTION



MOLDED
CONSTRUCTION

EXHIBIT "A"

HP OfficeJet
Personal Printer/Fax/Copier

Fax Log Report

Feb-28-03 11:26 PM

Last 30 faxes

Identification	Result	Pages	Type	Date	Time	Duration	Diagnostic
	Error	00	Received	Feb-20	09:47A	00:00:36	001000000000403
	Error	00	Received	Feb-21	09:14A	00:00:36	001000000000403
	Error	00	Received	Feb-23	02:42P	00:00:35	001000000000403
	Error	00	Received	Feb-23	02:43P	00:00:36	001000000000403
	Error	00	Received	Feb-24	12:42P	00:00:36	001000000000403
	Error	00	Received	Feb-24	05:48P	00:00:36	001000000000403
	OK	01	Received	Feb-24	07:36P	00:00:35	021500030000
	OK	01	Sent	Feb-24	09:22P	00:00:20	002586030022
	Error	00	Received	Feb-25	03:31P	00:00:36	001000000000403
	Error	00	Received	Feb-25	04:37P	00:00:36	001000000000403
	Error	00	Received	Feb-25	07:45P	00:00:36	001000000000403
	Error	00	Received	Feb-26	09:25A	00:00:36	001000000000403
	OK	01	Sent	Feb-26	02:39P	00:01:33	002784010022
	OK	07	Sent	Feb-26	03:01P	00:04:51	002584030022
	OK	06	Sent	Feb-26	03:51P	00:08:13	002584030022
	Error	00	Received	Feb-26	07:18P	00:00:36	001000000000403
	Error	00	Received	Feb-27	09:19A	00:00:36	001000000000403
	OK	01	Received	Feb-27	11:25A	00:00:46	021101430000
	Error	00	Received	Feb-27	04:06P	00:00:36	001000000000403
	Error	00	Received	Feb-27	05:23P	00:00:36	001000000000403
	Error	00	Received	Feb-28	09:13A	00:00:36	001000000000403
	OK	03	Sent	Feb-28	10:10A	00:02:05	002584030022
	Error	00	Received	Feb-28	12:46P	00:00:36	001000000000403
	Error	00	Received	Feb-28	02:15P	00:00:36	001000000000403
	OK	03	Sent	Feb-28	07:33P	00:01:44	002586030022
	OK	01	Sent	Feb-28	07:41P	00:00:21	002586030022
	OK	01	Sent	Feb-28	08:12P	00:00:25	002586030022
17033053597	Error	18	Sent	Feb-28	10:59P	00:09:37	022586030012551
17033053597	No answer	00	Sent	Feb-28	11:12P	00:00:00	002080000000
17033064195	OK	19	Sent	Feb-28	11:15P	00:10:56	002486030022

Attorney's
copy of log
for 02/28/03

HP OfficeJet
Personal Printer/Fax/Copier

Fax Log Report

Jun-26-03 10:25 AM

Last Fax

<u>Identification</u>	<u>Result</u>	<u>Pages</u>	<u>Type</u>	<u>Date</u>	<u>Time</u>	<u>Duration</u>	<u>Diagnostic</u>
17038729326	OK	39	Sent	Jun-26	09:59A	00:22:36	002586030022

1.50 2.5

copy of
Attorney's log
for 06/26/03
to Official
USPTO fax

703-872-9326

extra copy
of current
fax cover sheet
also mistakenly
sent - with
incorrect Examiner
Phone #
(and line through
incorrect #)

1 Applicant: Timothy M. Bronson and Brian V. Fiala
2 Serial Number: 10/044,108
3 Date Filed: January 11, 2002
4 Title: Valley Truss Uplift Resistance Strap With Wedge and Method of Use
5 Examiner: Christy M. Green
6 Group Art Unit: 3635

7
8 MARKED-UP COPY OF BRIEF DESCRIPTION OF THE DRAWINGS AND THE
9 DETAILED DESCRIPTION OF PREFERRED EMBODIMENTS
10 (additional text is underlined)
11

12 BRIEF DESCRIPTION OF THE DRAWINGS

13 Fig. 1 is perspective view of a first embodiment of the present invention having a planar base
14 member, a web member upwardly extending from the base member at an acute angle, a wedge
15 positioned within the acute angle, and a plurality of fastener holes through the web member and
16 the opposing ends of the base member.

17 Fig. 2 is a front view of two first embodiment uplift resistance straps attached between a
18 manufactured valley truss and two standard manufactured wood roof trusses supporting it.

19 Fig. 3 is a perspective view of the first embodiment connected between a vertically extending
20 piece of construction material with a non-beveled bottom end, and the top chord of a standard
21 manufactured wood roof truss.

22 Fig. 4 is a perspective view of the first embodiment connected between a non-beveled
23 horizontally extending bottom chord of a manufactured valley truss and the top chord of a
24 standard manufactured wood roof truss.

25 Fig. 5 is a top view of a second embodiment of the present invention in a substantially flat,
26 unfolded condition.

27 Fig. 6 is a top view of the second embodiment in a partially folded condition.

28 Fig. 7 is also a top view of the second embodiment in a partially folded condition.

29 Fig. 8 is also a top view of the second embodiment in a partially folded condition.

30 Fig. 9 is a top view of the second embodiment in a nearly complete folded condition.

1 Fig. 10 is a top view of a third embodiment of the present invention in a substantially flat,
2 unfolded condition.

3 Fig. 11 is a top view of the third embodiment in a partially folded condition.

4 Fig. 12 is a top view of the third embodiment in a nearly complete folded condition.

5 Fig. 13 is a perspective view of a fourth embodiment of the present invention in a partially folded
6 condition.

7 Fig. 14 is a perspective view of the fourth embodiment in a nearly complete folded condition.

8 Fig. 15 is a perspective view of the fourth embodiment in its completely folded condition ready
9 for use.

10 Fig. 16 is a top view of the fourth embodiment in a substantially flat, unfolded condition.

11 Fig. 17 is a perspective view of the fourth embodiment connected between a vertically extending
12 piece of construction material with a non-beveled bottom end, and the top chord of a standard
13 manufactured wood roof truss.

14 Fig. 18 is a perspective view of the forth embodiment connected between a non-beveled
15 horizontally extending bottom chord of a manufactured valley truss and the top chord of a
16 standard manufactured wood roof truss.

17 Fig. 19 is a side view of the fourth embodiment having a nail inserted through the lower portion
18 of the web member, the wedge, and the base member.

19 Fig. 20 is a perspective view of a several present invention uplift resistance straps each connected
20 between the horizontally extending bottom chord of a manufactured valley truss and the top
21 chord of a standard manufactured wood roof truss.

22 Fig. 21 is a perspective view of two perpendicularly oriented roof structures having a valley
23 therebetween in which the present invention could be used to provide uplift resistance.

24 Fig. 22 is a perspective view of a fifth embodiment of the present invention having a molded
25 construction.

DETAILED DESCRIPTION OF PREFERRED EMBODIMENTS

The present invention provides uplift resistance to roof construction where valleys occur. two examples of which are shown in Figs. 20 and 21. Fig. 20 shows the construction of what could be a small porch roof connected to a larger roof structure behind it, with the standard roof trusses 18 below bearing perpendicular to the overlaying porch trusses 16. This overlap of roof and porch trusses, to fill in the roof plane, creates a valley. In contrast, Fig. 21 shows two full roof structures connected to one another in a T-shaped configuration. The fill area where the roof structures overlap and a set of roof trusses 18 below bear perpendicular to a second overlaying set of roof trusses 16, also comprises a valley. In addition to uplift resistance, the present invention would also provide a built-in wedge configured to level the overlaying valley trusses, without a need for beveling the bottom chord of each valley truss or a need for the time-consuming on-site manufacture and installation of stand-alone wedges that allow a solid connection between supported valley trusses 16 and the sloping top chords of the standard roof trusses 18 beneath them. Further, the present would replace an elongated prior art tie-down strap that must be attached to adjoining trusses through a hole made on-site in the roof sheathing adjacent to the truss intersection. Thus, connection of the elongated prior art tie-down straps is accomplished in a separate step following the step of attaching the valley truss to underlying standard roof trusses. Further, installation of the elongated tie-down strap typically requires two people, with one person positioned above the roof plane to connect the upper portion of the elongated tie-down strap to the valley truss and another person below the roof plane to connect the lower portion of the elongated tie-down strap to the standard roof truss, or the same person to sequentially perform the upper and lower tie-down strap connections. In contrast, installation of the present invention is faster as it is used directly in the connection of a valley truss to each of the standard roof trusses supporting it, so that connection, leveling, and uplift resistance

1 requirements are all satisfied in a single installation step. The present invention, already having a
2 pre-formed wedge incorporated therein, also eliminates a need for additional steps involving the
3 creation and connection of a stand-alone wedge or subsequent tie-down connection at each
4 intersection of a manufactured valley truss to a standard manufactured wood roof truss. It is
5 contemplated for the present invention to be made of rigid materials and have a unitary
6 construction. However, the present invention can be made from plastic, nylon and other
7 materials formed through molded construction, or in the alternative made from a stamped piece
8 of rigid material, preferably galvanized steel, that is pre-formed into the approximate
9 configuration shown in Fig. 1. The wedge of the present invention, pre-formed at a designated
10 angle appropriate to the slope of the top chord in each of the underlying standard roof trusses
11 with which it is contemplated for use, provides leveling for an overlaying valley truss without the
12 costly, labor-intensive process of beveling the bottom surface of each valley truss, either during
13 manufacture or on-site, or the creation and connection of stand-alone wedges that are connected
14 between the bottom chord of a valley truss and the top chord of each standard roof truss
15 supporting it. The wedge can be solid or hollow, depending upon the materials used for its
16 construction. Further, since holes are pre-formed through the upwardly extending web member
17 and the base member of the present invention, an installer is not confronted with the additional
18 time delays resulting from replacement of wooden wedges that split or crack during fastener
19 attachment.

20 Fig. 1 shows a first embodiment 2 of the present invention having a planar base member
21 with a first end 4 and a second end 6, and a web member 10 upwardly extending from second end
22 6 to form an acute angle 12 relative to first end 4. Although web member 10 appears to have
23 approximately the same length dimension as first end 4 and second end 6, web member 10 could
24 be shorter or longer than first end 4 and second end 6, with the length of web member 10 being
25 determined by the governing uplift resistance code requirement. An embodiment where second
26 end 6 is shorter than web member 10 and first end 4 has been omitted, is shown in Fig. 15. Fig. 1

1 also shows a wedge 8 positioned within acute angle 12, and connected between first end 4 and
2 web member 10. The height of the taller end of wedge 8 would vary according to different pitch
3 applications. Also, although not limited thereto, the upper surface of wedge 8, which provides
4 the seat area for an overlaying valley truss 16, would preferably have a minimum surface area of
5 approximately one-and-one-half square inches. Fig. 1 further shows two fastener holes 14 in web
6 member 10, two fastener holes 14 in second end 6, and one fastener hole 14 in first end 4. The
7 number, size, spaced-apart distance, alignment, and configuration of fastener holes 14 are not
8 critical, and at a minimum would be sufficient to meet nailing and uplift resistance requirements
9 of the local or regional building code. Fig. 1 also shows the distal ends of first end 4, second end
10 6, and web member 10, each being substantially rectangular in configuration and having
11 chamfered edges to help resist bending the could otherwise occur from uplift. In addition to the
12 configuration of corners appearing to be cut off at an approximate 45° angle, it is considered to be
13 within the scope of the present invention for the distal ends of first end 4, second end 6, and web
14 member 10, to also have the rounded configuration shown in Figs. 5-9, or other linear, arcuate, or
15 curvilinear configuration. It is contemplated that first embodiment 2 would be made from
16 molded construction, using metal, plastic, nylon, or any other material permitted by code. One
17 preferred plastic material is [polycarbamate] polycarbonate. Also, although not limited thereto
18 and only provided as an example, it is contemplated that the length dimension of first
19 embodiment 2, from the distal end of first end 4 to the distal end of second end 6, would be a
20 minimum of approximately four inches and a maximum of approximately twelve inches. The
21 first embodiment shown in Fig. 1 could represent either a molded or folded uplift resistance
22 strap. The taller end of wedge 8, which is shown in Fig. 1 in a position facing second end 6, has
23 an open configuration expected in folded embodiments formed from the unfolded stamped
24 configurations of second embodiment 24 and third embodiment 26, shown in Figs. 5 and 10,
25 respectively, the vertical support for wedge 8 being derived from its rigid side structures. In
26 contrast, the embodiments of the present invention made through molded construction could

1 similar to that shown in Fig. 1.

2 Fig. 2 shows first embodiment 2 attached between the bottom chord of a valley truss 16
3 and the top chord of a standard roof truss 18 supporting it. Although two first embodiment 2
4 attachments are shown, the number of first embodiments 2 connected between valley truss 16
5 and standard roof trusses 18 would be determined by code. The upstanding web member 10 in
6 each first embodiment 2 is connected to the downwardly facing side of a supported valley truss
7 16 through fasteners (not shown) inserted through fastener holes 14, while the second end 6 of
8 each first embodiment 2 is connected to the top cord of the standard roof truss 18 supporting the
9 same valley truss 16, also via a fastener (not shown) inserted through each fastener hole 14
10 present in the planar base member of first embodiment 2, which includes second end 6 and first
11 end 4 (not visible in Fig. 2). When the present invention is relied upon to provide a wedge 8 for
12 non-beveled trusses 16, one first embodiment 2 would become connected at every intersection of
13 valley truss 16 to standard roof trusses 18. As shown in Fig. 2 and mentioned above, the uplift
14 resistance straps of first embodiment 2 are only secured on the side of valley truss 16 that is
15 facing the downward sloping ends of the standard roof trusses 18 supporting it.

16 Fig. 3 shows first embodiment 2 connected between a vertically extending piece of
17 construction material 20 with a non-beveled bottom end 22, and the top chord of a standard roof
18 truss 18. Fig. 3 shows second end 6 attached to the portion of standard roof truss 18 in a
19 position downwardly extending below construction material 20, and web member 10 attached to
20 the side of construction material 20 that faces the downwardly extending end of standard roof
21 truss 18 supporting it. Fig. 3 further shows the non-beveled bottom end 22 of construction
22 material 20 supported in a substantially level position upon wedge 8, and first end 4 positioned
23 against the top chord of the portion of standard roof truss 18 upwardly extending beyond
24 construction material 20.

25 Fig. 4 shows first embodiment 2 connected between a horizontally extending bottom
26 chord of a manufactured valley truss 16 and the top chord of a standard roof truss 18. As shown

1 in Fig. 4, first embodiment 2 is only secured to valley truss 16 via web member 10, and only on
2 the vertical side of valley truss 16 that is facing the downwardly extending ends of standard roof
3 trusses 18. Connection between first embodiment 2 and the top chord of a standard roof truss 18
4 is accomplished via the planar base member of first embodiment 2, which comprises second end
5 6 and first end 4. This is in contrast to the fourth embodiment 32 shown in Fig. 19, wherein the
6 bottommost fastener hole 14b in web member 10 is used in part to attach web member 10 to the
7 top chord of the supporting standard roof truss 18. In Fig. 4, second end 6 is placed in a position
8 adjacent to valley truss 16 and downwardly extending from valley truss 16 with fasteners inserted
9 through fasteners holes 14 and secured between first embodiment 2 and standard roof truss 18,
10 while first end 4 is placed in a position adjacent to valley truss 16 and upwardly extending
11 therefrom, also being secured by fasteners inserted through fasteners holes 14. As shown in Fig.
12 4, wedge 8 is positioned under the bottom chord of valley truss 16. The degree of incline
13 provided by wedge 8 can be varied during manufacture, to accommodate a difference in roof
14 pitch. Also, although not critical, Fig. 4 shows first end 4 and second end 6 extending the full
15 width of standard roof truss 18. The width and thickness dimensions of first end 4, second end 6,
16 and web member 10 can vary, so as to allow a balance between the need for cost-efficient
17 construction and compliance with the governing code requirements. The relative dimensions of
18 first end 4, second end 6, and web member 10 can also vary, as can the number and positioning
19 of fastener hole 14 therethrough. Also, although steel and selected plastics, such as
20 [polycarbamate] polycarbonate, are preferred for the manufacture of first embodiment 2, other
21 materials can be used as long as they meet the necessary strength requirements to satisfy the
22 governing uplift resistance code.

23 Figs. 5-9 show a second embodiment 24 of the present invention in an unfolded
24 condition, and various phases of folding. In Figs. 5-9 the distal perimeter of first ends 4A and
25 4B, second ends 6A and 6B, as well as web member 10 are shown to have a rounded
26 configuration. Although a blunt perimeter is favored for safety considerations to avoid injury,

1 other perimeter configurations are also considered to be within the scope of the present invention.
2 such as a rectangular configuration and the rectangle with chamfered ends shown in Figs. 10-12
3 for web 10, first side 4 and second side 6, wherein the corners of are all cut off at an approximate
4 45° angle. Fig. 5 shows second embodiment 24 in a substantially flat, unfolded condition. The
5 arrows above web member 10 show that as the second embodiment 24 takes its final form, web
6 member 10 would be moved rearwardly and away from second ends 6A and 6B. The arrows
7 adjacent to second ends 6A and 6B, show that as the second embodiment 24 takes its final form,
8 second ends 6A and 6B would each be moved forwardly and toward one another. Figs. 6, 7, and
9 8 show second embodiment 24 in a partially folded condition, with each successively higher
10 numbered illustration showing second embodiment 24 progressively closer to its usable
11 configuration, while Fig. 9 shows second embodiment 24 in a nearly complete folded condition.
12 Fig. 6 shows second ends 6A and 6B closer together than in Fig. 5, with web member 10 more
13 rearwardly positioned than in Fig. 5. Fig. 7 shows second end 6B being inwardly folded and
14 rotated approximately 180° from its original pre-folded position, with second end 6B being
15 poised for a similar 180° inwardly folded rotation. Although second end 6B is shown undergoing
16 the 180° rotation first, the order of such rotation is not critical. Fig. 8 shows both second ends 6A
17 and 6B after undergoing a near 180° rotation, but not yet aligned with one another as they would
18 be when second embodiment 24 has reached its final configuration. Fig. 10 shows second end
19 6B and first end 4B aligned with web member 10, with second end 6A and first end 4A needing
20 approximately 90° more rotation for second embodiment 24 to reach its usable configuration,
21 similar to that shown in Fig. 1. When folding is complete, wedge 8 in second embodiment 24
22 would have the same hollow configuration shown in Fig. 1. It is contemplated for second
23 embodiment 24 to be made from rigid material, such as steel, plastic, or nylon, and have a
24 substantially uniform thickness.

25 Figs. 10, 11, and 12 respectively show a third embodiment 26 of the present invention in
26 a substantially flat unfolded condition, an intermediate folded condition, and a nearly complete

1 folded condition. It is contemplated for third embodiment 26 to be made from rigid material,
2 such as steel, nylon, or plastic, and have a substantially uniform thickness. Figs. 10-12 further
3 show the planar base member having first end 4 and second end 6, and web member 10 all of
4 similar length and width dimension, each as being substantially rectangular with chamfered distal
5 ends, wherein the corners are all cut off at an approximate 45° angle. Fig. 10 shows third
6 embodiment 26 in a substantially flattened condition, prior to folding. In Fig. 11, the arrows
7 above web member 10 show that as the third embodiment 26 takes its final form, web member
8 10 would be moved rearwardly and away from wedge 8. The arrows adjacent to second end 6
9 and first end 4, show that as the third embodiment 26 takes its final form, second end 6 and first
10 end 4 would each be moved forwardly and toward one another. Fig. 12 shows that first end 4
11 and second end 6 also undergo an approximate 180° rotation relative to their original pre-folded
12 conditions, prior to the third embodiment 26 reaching its usable configuration. Either second end
13 6 or first end 4 can be folded in advance of the other, or both can be folded at once since there is
14 no overlap of one member relative to the other similar to that occurring in the folding of second
15 embodiment 24. Fig. 12 shows second end 6 and first end 4 almost aligned with one another as
16 they would be when third embodiment 26 has reached its final configuration, similar to that
17 shown in Fig. 1, with third embodiment 26 having a hollow wedge 8. The adjoining surfaces of
18 first end 4 and second end 6, which extend diagonally and form the bottom surface of wedge 8,
19 can be bonded or welded to one another during manufacture, if needed to satisfy the governing
20 code requirements.

21 Figs. 13-19 show a fourth embodiment 32 of the present invention in an unfolded
22 condition, and various phases of folding, as well as in positions of use. Figs 13 and 14 show
23 fourth embodiment 32 in partially folded conditions, while Fig. 16 shows fourth embodiment 32
24 in a substantially flat, unfolded condition and Fig. 15 shows fourth embodiment 32 in its
25 completely folded condition ready for use. Fig. 15 shows the present invention having an
26 upstanding web member 10, a hollow wedge 8 having an upper surface 28 extending forwardly

1 from web member 10, a rearwardly extending second end 6, and several fastener holes 14.
2 Second end 6 is significantly shorter than web member 10, and in fourth embodiment 32 no first
3 end 4 is present. Another difference in fourth embodiment 32 is that wedge 8 has a vertical back
4 wall containing fastener hole 14b1, instead of the laterally positioned walls shown in Fig. 1. A
5 further difference between fourth embodiment 32 and the other illustrated embodiments of the
6 present invention is that fourth embodiment 32 contains fastener holes 14b, 14c, 14b1, and 14c1,
7 which collectively allow a fastener, such as fastener 34 in Fig. 19, to be secured through wedge 8.
8 Although not limited thereto, Fig. 15 shows three fastener holes 14 through web member 10,
9 with the upper holes being offset from one another as well as from the laterally centered bottom
10 fastener holes 14. While the angle 12 between upper wedge surface 28 and web member 10 is
11 shown in Fig. 15 to be approximately 90° , the intersection between the bottom surface of wedge
12 8 and web member 10 typically represents an acute angle more pronounced than illustrated. Fig.
13 16 shows fourth embodiment 32 in its flattened, unfolded condition. Moving from left to right in
14 the illustration of unfolded fourth embodiment 32 in Fig. 16, one first encounters web member
15 10 with three fastener holes, the bottommost of which is designated by the number 14b. To the
16 right of web member 10, one next encounters rearwardly extending second end 6, with one
17 centrally positioned fastener hole 14a. The bottom surface 30 of fourth embodiment 32 is
18 situated to the right of rearwardly extending second end 6 and contains two fastener holes 14a1
19 and 14c. The upper surface of wedge 8 extends to the right of bottom surface 30 and has no
20 fasteners holes 14. The remaining two sections of fourth embodiment 32 having centered
21 fastener holes 14b1 and 14c1 are unnumbered and are reinforcement members for wedge 8, the
22 one which contains fastener hole 14b1 forming a vertically extending back wall of wedge 8
23 during use. Thus, when fully formed, the structure of wedge 8 in the fourth embodiment would
24 comprise open sides, a double layer of vertical support at its taller end, a partially doubled bottom
25 surface 30, and aligned fastener holes 14b, 14b1, 14c, and 14c1 that would allow a fastener, such
26 as fastener 34 in Fig. 19 to pass through both layers at the taller end of wedge 8, exit through

1 both layers forming the bottom surface 30 of wedge 8, and enter the top chord of the standard
2 roof truss 18 upon which the fourth embodiment 32 is supported during use. To fold fourth
3 embodiment 32 into its usable configuration, the lower end of web member 10 is brought into
4 contact with bottom surface 30 so that fastener holes 14a and 14a1 become aligned to form
5 second end 6. As this occurs, rearwardly extending second end 6 becomes superimposed upon a
6 portion of bottom surface 30. In a separate step, the opposing end on fourth embodiment 32 is
7 folded to form wedge 8, with fastener hole 14b1 becoming aligned with fastener hole 14b in the
8 lower end of web member 10, and fastener hole 14c1 becoming aligned with fastener hole 14c in
9 bottom surface 30. Arrows in Figs. 13 and 14 show the directions of folding. Thus, it is
10 contemplated for four fasteners, such as fastener 34 in Fig. 19 that is configured as a nail, to be
11 used for securing fourth embodiment 32 in place during use. A first fastener 34 would extend
12 through two fastener holes, 14a and 14a1 to connect second end 6 to the downwardly extending
13 portion of the top chord of a standard roof truss 18. A second fastener 34 would extend through
14 two fastener holes, 14b and 14b1, further extend through wedge 8, and then finally through two
15 additional fastener holes, 14c1 and 14c to connect web member 10 and wedge 8 to the top chord
16 of the same standard roof truss 18. The final two nails 34 would each extend through a different
17 one of the upper fastener holes 14 in web member 10 to connect web member 10 to the vertically
18 extending side of valley truss 16 facing second end 6. Fourth embodiment 32 has the simplest
19 construction, and would produce the least material waste during manufacture. It is contemplated
20 for wedge 8 to be manufactured with varying pitch, depending upon the application, and for
21 fourth embodiment 32 to be made from rigid material, such as steel, plastic, nylon, and have a
22 substantially uniform thickness. As an alternative to folded construction, a molded embodiment
23 similar to that shown in Fig. 15 is also considered to be within the scope of the present invention,
24 and which would preferably have a solid wedge 8, as well as a fastener hole 14 through wedge 8
25 in a similar position to that shown for fastener 34 in Fig. 19. Although not limited thereto, such a
26 molded embodiment could be made from plastic material, such as [polycarbonate]

1 polycarbonate. Fig. 17 shows fourth embodiment 32 connected between a vertically extending
2 piece of construction material 20 with a non-beveled bottom end 22, and the top chord of a
3 standard manufactured wood roof truss 18, while Fig. 18 shows forth embodiment 32 connected
4 between a non-beveled horizontally extending bottom chord of a manufactured valley truss 16
5 and the top chord of a standard manufactured wood roof truss 18. Although the upper surface 28
6 of wedge 8 is not marked in Fig. 17 or Fig. 18 for clarity of illustration, both Figs 17 and 18 show
7 upper wedge surface 28 positioned entirely under the superimposed construction material,
8 vertically extending piece of construction material 20 or manufactured valley truss 16.
9 respectively. Fig. 22 shows a fifth preferred embodiment of the present invention, similar in
10 configuration to that shown in Fig. 15 and having a molded construction.

11 Fig. 20 shows several present invention uplift resistance straps, such as first embodiments
12 2, each connected between the horizontally extending bottom chord of a manufactured valley
13 truss 16 and the top chord of a standard roof truss 18. Fig. 21 is a perspective view of two
14 perpendicularly oriented roof structures having a valley therebetween where the present invention
15 could be used for uplift resistance. As shown in Fig. 20, the web members 10 of first
16 embodiments 2 are only secured on the vertically extending side of valley trusses 16 facing the
17 downwardly extending ends of standard roof trusses 18. It is contemplated that the web members
18 10 of the second embodiments 24, the third embodiments 26, and the fourth embodiments 32
19 would also be connected to the sides of valley trusses 16 the downwardly extending ends of
20 standard roof trusses 18, with the bottommost fastener hole 14b of fourth embodiments 32 being
21 used with a fastener 34 that extends into the top chord of a supporting standard roof truss 18 and
22 thereby connects web member 10 and wedge 8 to the supporting standard roof truss 18.